



Applications where FEP tubing is chosen usually require more clarity, flexibility or a lower heat shrinkable temperature than PTFE.

Inside Diameter (inches)				Wall Dimensions (inches)						
				Standard Wall		Thin Wall		Light weight wall		
AWG Size	Min.	Nom.	Max	Nom.	Tol.	Nom.	Tol.	Nom.	Tol.	Packaging
32	0.008	0.010	0.012	0.005	+/- .002	0.005	+/- .002	-	-	1000' Spools
30	0.010	0.012	0.015	0.009	+/- .002	0.009	+/- .002	0.006	+/- .002	1000' Spools
28	0.013	0.015	0.018	0.009	+/- .002	0.009	+/- .002	0.006	+/- .002	1000' Spools
26	0.016	0.018	0.021	0.009	+/- .002	0.009	+/- .002	0.006	+/- .002	1000' Spools
24	0.020	0.022	0.026	0.012	+/- .002	0.010	+/- .003	0.006	+/- .002	1000' Spools
23	0.023	0.026	0.029	0.012	+/- .002	0.010	+/- .003	0.006	+/- .002	1000' Spools
22	0.026	0.028	0.032	0.012	+/- .002	0.010	+/- .003	0.006	+/- .002	1000' Spools
21	0.029	0.032	0.035	0.012	+/- .002	0.010	+/- .003	0.006	+/- .002	1000' Spools
20	0.032	0.034	0.038	0.016	+/- .003	0.012	+/- .003	0.006	+/- .002	1000' Spools
19	0.036	0.038	0.042	0.016	+/- .003	0.012	+/- .003	0.006	+/- .002	1000' Spools
18	0.040	0.042	0.046	0.016	+/- .003	0.012	+/- .003	0.006	+/- .002	1000' Spools
17	0.045	0.047	0.052	0.016	+/- .003	0.012	+/- .003	0.006	+/- .002	1000' Spools
16	0.051	0.053	0.058	0.016	+/- .003	0.012	+/- .003	0.006	+/- .002	1000' Spools

15	0.057	0.059	0.065	0.016	+/- .003	0.012	+/- .003	0.006	+/- .002	1000' Spools
14	0.064	0.066	0.072	0.016	+/- .003	0.012	+/- .003	0.008	+/- .002	500' Spools
13	0.072	0.076	0.081	0.016	+/- .003	0.012	+/- .003	0.008	+/- .002	500' Spools
12	0.081	0.085	0.091	0.016	+/- .003	0.012	+/- .003	0.008	+/- .002	500' Spools
11	0.091	0.095	0.101	0.016	+/- .003	0.012	+/- .003	0.008	+/- .002	500' Spools
10	0.102	0.106	0.112	0.016	+/- .003	0.012	+/- .003	0.008	+/- .002	500' Spools
9	0.114	0.118	0.124	0.020	+/- .004	0.015	+/- .003	0.008	+/- .002	250' Spools
8	0.129	0.133	0.139	0.020	+/- .004	0.015	+/- .003	0.008	+/- .002	-
7	0.144	0.148	0.155	0.020	+/- .004	0.015	+/- .003	0.008	+/- .003	-
6	0.162	0.166	0.174	0.020	+/- .004	0.015	+/- .003	0.010	+/- .003	-
5	0.182	0.186	0.195	0.020	+/- .004	0.015	+/- .003	0.010	+/- .003	-
4	0.204	0.208	0.218	0.020	+/- .004	0.015	+/- .003	0.010	+/- .003	-
3	0.229	0.234	0.244	0.020	+/- .004	0.015	+/- .003	0.010	+/- .003	-
2	0.258	0.263	0.273	0.020	+/- .004	0.015	+/- .003	0.010	+/- .003	-
1	0.289	0.294	0.294	0.020	+/- .004	0.015	+/- .003	0.010	+/- .003	-
0	0.325	0.330	0.342	0.020	+/- .004	0.015	+/- .003	0.012	+/- .003	-